630mm 3 Install the Automatic Water Saver Top Push the touchless addon up, it will self-lock to complete the installation. (You can adjust and rotate the addon to fit the position you need) Installation of external threaded faucets Installation of internal threaded adapters 105mm Produced by Xiaoda in China Supplier's Declaration of Conformity Basic specification The touchless faucet addon strictly implements the three packs of after-sales service based on the ${\mathbb Q}$ Law of the People's Republic of China on Protection of Consumer Rights and Interests ${\mathbb Q}$ and the ${\mathbb Q}$ Product Quality Law of the People's Republic of China ${\mathbb Q}$, which includes: 1. Leakage after installation Product Name: Automatic Water Saver Saver Top (1) Check if the sealing ring is installed correctly. Model Number: HD-ZNJSQ-01, HD-ZNJSQ-02 2. No water running out when your hand are close to the sensor Report No: ES190313987E Do not clean the body of the product with strong acid-based detergent. Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver. Company Name: Wuhan Smartda Electronic Technology Co.,Ltd (4) Check the battery power. Do not install the product near high-temperature objects. Manufacturer : Wuhan Smartda Electronic Technology Co., Ltd. Address: Room 101,Unit 2,Building 7,NO.1 Xincheng,Xiantao,Hubei Province Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Address: No. 1 of Xincheng, Xiantao City, Hubei Province, China 3. Water running intermittently or continuously Consult the dealer or an experienced radio TV technician for help. Version number : 20190304 E-mail: coco.gao@smartda.cn Phone No.: 400-088-6288 (1) Check if your hand is in the operating distance . Executive Standard : CJ/T194-2014 Non-warranty policy (2) Check if the side sensing mode is triggered by mistake when the bottom sensing mode is used, which will lead to continuous water running. The current water running can be disabled by sensing the side sensor again. (3) Check if there are any water drops residue on the bottom or side sensor window. Applied Standards Part 15 Subpart B - Section 15.107 and 15.109 ANSI C63.4:2014 4. Why are the sensor distances vary depending on different objects If the EUT was tested with special shielded cables the operators manual for such product shall also contain the following statements or their equivalent: Shielded interface cables and/or AC power cord, if any, must be used in order to comply with the emission limits. 2. Damage caused by maintaining by an unauthorized service provider. 5. Is there a hidden danger of flooding? (1) The product is equipped with anti-overflow protection design, Water flow is turned off automatically 20 seconds after the bottom sensor is activated and 3 minutes after the side sensor is activated to prevent accidents. (2) The addon is closed to prevent continuous water running even if no power due to a battery failure. (3) It is recommended to close your tap if you will not use it for a long time.

物料编号: 0000000

专色: PANTONE Cool Gray 11C

商品ID	SKU编码	商品名称	69码	产品型号
		小达感应水龙头		

历史 版本号: 修改点: 修改点: 修改人: 版本号: 版本号: 版本号: 版本号: 版本号: 修改点: 修改点: 修改人: 修改人: 修改人: 修改人: 修改人: 版本号: 版本号: 版本号: 修改点: 修改点: 修改点: 修改点: 修改人: 修改人:

小米生态链产品包装图纸

图纸提 供单位

材质:太空梭哑粉105g

工艺: 单色双面印刷、风琴6折

材质工艺要求

印刷要求: 色相正确、印迹牢固、套印准确、

各色套印不露杂色,套印误差≤ 0.1mm

说明书边角为直角,不做R角

纹 理 方 向

备注

项目名称	小达感应节水器				
版本号	C-20190304				
设计时间	C-20190304				
设计师					
设计师					
设计师					

比例 !"! 单位 ##