



TEST REPORT

Product Name: Outdoor electric heating equipment
Trademark: N/A
Model Number: WS-GF0126
WS-G0120C, WS-GA0340B, WS-GA680A, WS-GA800A,
WS-GA840A, WS-GA850A, WS-GA860A, WS-GA690A,
WS-SE220L, WS-SE330LA, WS-SE336L, WS-SE360,
WS-SE380, WS-X04AF, WS-X01D, WS-Y06AF, WS-Y01A,
WS-W01A, WS-N002, WS-N003, WS-WN100, WS-WB100,
WS-WB200, WS-WB300
Prepared For: Wuxi Warmspace Technology Co.,Ltd
Address: Flat804, Block 3 No.2018, Lihu Avenue, Binhu District, Wuxi,
Jiangsu Province, P.R. China
Manufacturer: Wuxi Warmspace Technology Co.,Ltd
Address: Flat804, Block 3 No.2018, Lihu Avenue, Binhu District, Wuxi,
Jiangsu Province, P.R. China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: BCTC Building & 1-2F, East of B Building, Pengzhou
Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong
Street, Bao'an District, Shenzhen, China
Sample Received Date: Apr. 01, 2019
Sample tested Date: Apr. 01, 2019 to Apr. 02, 2019
Issue Date: Apr. 03, 2019
Report No.: BCTC-FY190301635E
Test Standards: EN 55014-1:2017, EN 55014-2:2015
Test Results: PASS

Compiled by:

Kelsey Tan

Kelsey Tan

Reviewed by:

Eric Yang

Eric Yang

Approved by:

Zero Zhou

Zero Zhou/Manager



The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.



TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration	6
4.3 Support Equipment	6
4.4 Test Mode	7
5. TEST FACILITY AND TEST INSTRUMENT USED	8
5.1 Test Facility	8
5.2 Test Instrument Used	8
6. RADIATED DISTURBANCE TEST	10
6.1 Block Diagram Of Test Setup	10
6.2 Limits	10
6.3 Test Procedure	10
6.4 Test Results	11
7. IMMUNITY TEST OF GENERAL THE PERFORMANCE CRITERIA	13
8. ELECTROSTATIC DISCHARGE (ESD)	14
8.1 Test Specification	14
8.2 Block Diagram of Test Setup	14
8.3 Test Procedure	14
8.4 Test Results	15
9. RADIO FREQUENCY ELECTROMAGNETIC FIELDS(RS)	16
9.1 Test Specification	16
9.2 Block Diagram of Test Setup	16
9.3 Test Procedure	16
9.4 Test Results	17
10. EUT PHOTOGRAPHS	18
11. EUT TEST SETUP PHOTOGRAPHS	20

(Note: N/A means not applicable)



1. VERSION

Report No.	Issue Date	Description	Approved
BCTC-FY190301635E	Apr. 03, 2019	Original	Valid



2. TEST SUMMARY

The Product has been tested according to the following specifications:

EMISSION		
Standard	Test Item	Test result
EN 55014-1	Conducted emissions from the AC mains power ports	N/A ¹
EN 55014-1	Asymmetric mode conducted emissions	N/A ⁴
EN 55014-1	Conducted differential voltage emissions	N/A ⁵
EN 55014-1	Radiated emissions	Pass

IMMUNITY (EN 55014-2)		
Standard	Test Item	Test result
IEC 61000-4-2	Electrostatic discharge (ESD)	Pass
IEC 61000-4-3	Continuous RF electromagnetic field disturbances(RS)	Pass
IEC 61000-4-4	Electrical fast transients/burst (EFT)	N/A ¹
IEC 61000-4-5	Surges	N/A ¹
IEC 61000-4-6	Continuous induced RF disturbances (CS)	N/A ¹
IEC 61000-4-6	Broadband impulse noise disturbances, repetitive	N/A ²
IEC 61000-4-6	Broadband impulse noise disturbances, isolated	N/A ²
IEC 61000-4-8	Power frequency magnetic field (PFMF)	N/A ³
IEC 61000-4-11	Voltage dips and interruptions (DIPS)	N/A ¹

Remark:

1. The EUT is powered by the DC only , the test item is not applicable
2. Applicable only to CPE xDSL ports.
3. The Product doesn't contain any device susceptible to magnetic fields.
4. Applicable to ports listed above and intended to connect to cables longer than 3 m.
5. The Product has no antenna port.



3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test item	Value (dB)
Radiated Emission(30MHz~1GHz)	4.80



4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Ratings: DC 3.7V*2 2000mAh

Model differences: All models are identical except for the appearance color, the test model is WS-GF0126 and the test results are applicable to other tests.

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

No	Device Type	Brand	Model	Series No.	Data Cable	Power Cord
1.	---	---	---	---	---	---

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



4.4 Test Mode

Test item	Test Mode	Test Voltage
Radiated disturbance(30MHz-1GHz)	Working	DC 3.7V
Electrostatic discharge (ESD) B <input checked="" type="checkbox"/> Air Discharge: $\pm 8\text{kV}$ <input checked="" type="checkbox"/> Contact Discharge: $\pm 4\text{kV}$ <input checked="" type="checkbox"/> HCP & VCP: $\pm 4\text{kV}$	Working	DC 3.7V
Radio frequency electromagnetic fields(RS) A 80MHz-1000MHz, 3V/m,80%	Working	DC 3.7V
All test mode were tested and passed, only Radiated Emissions shows (*) is the worst case mode which were recorded in this report.		



5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

Radiated emissions Test (966 chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Mar. 03, 2018	Mar. 02, 2023
Receiver	R&S	ESR	102075	Jun. 20, 2018	Jun.19, 2019
Amplifier	Schwarzbeck	BBV9718	9718-309	Jun. 20, 2018	Jun.19, 2019
Amplifier	Schwarzbeck	BBV9744	9744-0037	Jun. 20, 2018	Jun.19, 2019
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	VULB9163-942	Jun. 23, 2018	Jun.22, 2019
Horn Antenna	SCHWARZBECK	BBHA9120 D	1201	Jun. 23, 2018	Jun.22, 2021
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Electrostatic discharge Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
ESD Tester	KIKISUI	KES4201 A	UH002321	Jun. 22, 2018	Jun. 21, 2019




Radio frequency electromagnetic fields Test

Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	GB42421440	Apr. 15, 2018	Apr. 14, 2019
Power sensor	Keysight	E9300A	US39211305	Apr. 15, 2018	Apr. 14, 2019
Power sensor	Keysight	E9300A	US39211659	Apr. 15, 2018	Apr. 14, 2019
Amplifier	SKET	HAP-8010 00M-250W	/	Aug. 13, 2018	Aug. 12, 2019
Amplifier	SKET	HAP-8010 00M-75W	/	Aug. 13, 2018	Aug. 12, 2019
Amplifier	SKET	HAP-8010 00M-50W	/	Aug. 12, 2018	Aug. 11, 2019
Stacked double Log.-Per. Antenna	Schwarzbeck	STLP 9129	077	Apr. 15, 2018	Apr. 14, 2019
Field Probe	Narda	EP-601	80256	Jun. 23, 2018	Jun. 22, 2019
Signal Generator	Agilent	N5181A	MY50143748	Jun. 20, 2018	Jun. 19, 2019
Software	SKET	EMC-S	1.2.0.18	\	\

6. RADIATED DISTURBANCE TEST

6.1 Block Diagram Of Test Setup



6.2 Limits

Frequency (MHz)	Quasi-peak limits at 3m dB(μ V/m)
30-230	40
230-1000	47

Note: The lower limit shall apply at the transition frequencies.


6.3 Test Procedure

- The Product was placed on the nonconductive turntable 0.8m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.



6.4 Test Results

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Horizontal
Test Voltage :	DC 3.7V	Test Mode:	Working



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1	*	45.3755	29.04	-15.11	13.93	40.00	-26.07	QP		
2		53.1313	27.10	-15.18	11.92	40.00	-28.08	QP		
3		98.1419	26.04	-16.62	9.42	40.00	-30.58	QP		
4		230.9068	24.37	-15.59	8.78	47.00	-38.22	QP		
5		463.9696	22.69	-9.68	13.01	47.00	-33.99	QP		
6		827.4934	22.01	-3.02	18.99	47.00	-28.01	QP		



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Vertical
Test Voltage :	DC 3.7V	Test Mode:	Working



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree
1	*	30.0000	37.03	-17.28	19.75	40.00	-20.25	QP		
2		45.0583	28.20	-15.13	13.07	40.00	-26.93	QP		
3		53.8818	27.98	-15.26	12.72	40.00	-27.28	QP		
4		98.1419	31.92	-16.62	15.30	40.00	-24.70	QP		
5		146.3735	29.26	-19.27	9.99	40.00	-30.01	QP		
6		543.2742	25.00	-7.85	17.15	47.00	-29.85	QP		

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



7. IMMUNITY TEST OF GENERAL THE PERFORMANCE CRITERIA


Product Standard	EN 55014-2:2015
CRITERION A	<p>The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
CRITERION B	<p>During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.</p> <p>After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.</p> <p>If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
CRITERION C	<p>Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.</p> <p>Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>

8. ELECTROSTATIC DISCHARGE (ESD)

8.1 Test Specification

Test Port	: Enclosure port
Discharge Impedance	: 330 ohm / 150 pF
Discharge Mode	: Single Discharge
Discharge Period	: one second between each discharge

8.2 Block Diagram of Test Setup



8.3 Test Procedure

- Electrostatic discharges were applied only to those points and surfaces of the Product that are accessible to users during normal operation.
- The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- The time interval between two successive single discharges was at least 1 second.
- The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the Product.
- Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- Air discharges were applied with the round discharge tip of the discharge electrode approaching the Product as fast as possible (without causing mechanical damage) to touch the Product. After each discharge, the ESD generator was removed from the Product and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the Product. The ESD generator was positioned vertically at a distance of 0.1 meters from the Product with the discharge electrode touching the HCP.



h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the Product were completely illuminated. The VCP (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the Product.

8.4 Test Results

Temperature:	23 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Mode:	Working
Test Voltage :	DC 3.7V		


Discharge Method	Discharge Position	Voltage (±kV)	Min. No. of Discharge per polarity (Each Point)	Required Level	Performance Criterion
Contact Discharge	Conductive Surfaces	4	10	B	A
	Indirect Discharge HCP	4	10	B	A
	Indirect Discharge VCP	4	10	B	A
Air Discharge	Slots, Apertures, and Insulating Surfaces	8	10	B	A
Note: N/A					

9. RADIO FREQUENCY ELECTROMAGNETIC FIELDS(RS)

9.1 Test Specification

Test Port	: Enclosure port
Step Size	: 1%
Modulation	: 1kHz, 80% AM
Dwell Time	: 1 second
Polarization	: Horizontal & Vertical

9.2 Block Diagram of Test Setup



9.3 Test Procedure

- The testing was performed in a fully-anechoic chamber. The transmit antenna was located at a distance of 3 meters from the Product.
- The frequency range is swept from 80MHz to 1000MHz, with the signal 80% amplitude modulated with a 1 kHz sine wave, and the step size was 1%.
- The test was performed with the Product exposed to both vertically and horizontally polarized fields on each of the four sides.



9.4 Test Results

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Mode:	Working
Test Voltage :	DC 3.7V		

Frequency	Position	Field Strength (V/m)	Required Level	Performance Criterion
80 - 1000MHz	Front, Right, Back, Left	3	A	A
Note: N/A				

10. EUT PHOTOGRAPHS

EUT Photo 1



EUT Photo 2



EUT Photo 3



11. EUT TEST SETUP PHOTOGRAPHS

Radiated emissions



ESD





RS



***** END OF REPORT *****